



DMVR

overview

- ◆ multi-voltage relay
- ◆ SPCO or DPCO output max. 6A
- ◆ coil voltage 24-240V~=
◆ LED indicators for supply voltage and output relay
- ◆ 22.5mm DIN rail mount housing

PLC interface relay 24-240Vac/dc

- Supply voltage on
- Supply voltage off
- Output relay contact closed
- Output relay contact open



specification

coil voltage	nominal voltage +10% / -15%		
duty cycle	100%		
relay type	1	3	
output relay spec	230V~	6A	10A
le AC-15*	120V~	4A	5A
le AC-15*	240V~	3A	4A
le DC-13*	24V=	2A	4A
expected life time	DPCO	SPCO	
mechanical	2 x 10 ⁶	resp.	1 x 10 ⁷ operations
electrical	1 x 10 ⁵	resp.	1 x 10 ⁵ operations
screws	pozidrive 1		
screw tightening torque	0,6...0,8Nm		
operating conditions	-20 to +60 °C non condensing		

* EN 60947-5-1 VDE 0435

ordering information

part no	supply	output	relay type		housing types
DMVR	24 - 240V~= 2VA	SPCO	3	-	A
DMVR2	24 - 240V~= 2VA	DPCO	1	-	B

other voltages on request