

# HTPC-850E

## overview

- ◆ **High performance**
- ◆ **High grade industrial components**
- ◆ **VIA C7 processor**
- ◆ **1 GB RAM**
- ◆ **Via PCI-Slot and CF-Card Adapter expandable**
- ◆ **Save softwaresystem with WindowsXP embedded**
- ◆ **no moving parts**



The maintenance-free and extremely efficient embedded HTPC-E family compines the frontUNIT with intelligentUNIT to a robust embedded PC.

The HTPC-E family offers you the ideal partner for the latest automation environment. A universal panel system will help you create and implement the most varied automation solutions.

With the operating system Microsoft WindowsXP embedded we have a save system for every application.

## specification

<b>Product type</b>	Compact embedded Panel PC
<b>General characteristics</b>	
processor	VIA C7 1Ghz fanless
chipset	VIA CN700 + 8237R plus
memory	1 GB DDR RAM
expansion slots	1 PCI Slot
operating system	Windows XP embedded
power supply	90-260Vac fanless
power consumption	35W with 15" Display
mass memory	DOM 2GB
additional drives	Compact Flash Reader
<b>Interfaces</b>	
LAN/Ethernet	10/100Mbps
USB	7x USB 2.0 (3x ext., 4x int.)
serial interface	2x RS232 (1x ext., 1x int.)
parallel interface	1x LPT1 (EPP/ECP/SPP)
keyboard/mouse	2x PS/2
<b>Ambient Conditions</b>	
temperature	+5°C to +45°C
relative humidity	5% to 80% at 25°C
vibration resistance	15G
shock resistance	50G

Size	15"	17"	19"	21"
a	400	460	472	540
b	310	360	383	440
c	90	95	95	110
d	370	429	440	509
e	290	337	363	406
<b>Weight</b>	ca. 10 kg	ca. 12 kg	ca. 13 kg	ca. 15 kg



## ordering information

part no	display	resolution	housing types
<b>HTPC-850E-15</b>	15" TFT-Display	1024x768 Pixel	special
<b>HTPC-850E-17</b>	17" TFT-Display	1280x1024 Pixel	special
<b>HTPC-850E-19</b>	19" TFT-Display	1280x1024 Pixel	special
<b>HTPC-850E-21</b>	21" TFT-Display	1600x1200 Pixel	special

\*Also other hardware and software configurations are available

