

TCV-W

overview


- ◆ AC or DC over or under voltage monitor with window function
- ◆ DPCO output max. 6A
- ◆ 3 measuring ranges 0.5 - 600V RMS
- ◆ level and hysteresis adjustments
- ◆ programmable latch/no latch alarm
- ◆ LED indicators for power supply, contact and reaction timer
- ◆ 45mm DIN rail mount housing



Function

- Control relay active
- Control relay passive
- Contact closed
- Contact open

- ① Threshold "Un"
- ② Hysteresis
- ③ Monitored current
- ④ Latch



ts... Start surge delay
tr... Reaction timer
T... LED indication reaction timer



On application of the supply voltage with N.O. Mode selected, the output relay pulls in and the timing period t_s starts.

Voltage monitor with no latch (auto reset) function


At the end of t_s when the measured voltage exceeds the window in either direction timing period t_r starts. At the end of t_r if the measurement still exceeds the set point the output relay changes over. The output relay resets immediately when the monitored voltage reaches the hysteresis set value.

Voltage monitor with latch (manual reset) function

At the end of t_s when the measured voltage exceeds the window in either direction, timing period t_r starts. At the end of t_r if the measurement still exceeds the set point the output relay changes over and remains in this condition, even when the measured voltage reaches the hysteresis set value. An external reset (S1) must be operated to reset the relay.



Supply Δ U Δ A1-A2



input	range	resistance	U_{EMAX} (20°C)
E1-M	0,5 - 10V	3,9 kOhm	30V
E2-M	3 - 60V	68 kOhm	130V
E3-M	30 - 600V	820 kOhm	660V

specification

supply voltage variation	nominal voltage +10% / -15%	
frequency range	48 - 63 Hz	
duty cycle	100%	
start surge delay	0 - 10s	
reaction time	0 - 5s	
reset time	< 100ms	
output relay specification	max. 6A 230V~	
	Ue/Ie AC-15	120V/4A 240V/3A
	Ue/Ie DC-13	24V/2A
expected life time	DPCO	SPCO
	mechanical	2 x 10 ⁶ resp. 1 x 10 ⁷ operations
	electrical	1 x 10 ⁵ resp. 1 x 10 ⁵ operations
screws	pozidrive 1	
screw tightening torque	0,6...0,8Nm	
operating conditions	-20 to +60 °C non condensing	
	* EN 60947-5-1 VDE 0435	

ordering information

part no	supply	output	sup. galv. iso*	HIQUEL US	housing types
TCV-W 230Vac	230V~ 2,5VA	DPCO	yes	yes	C
TCV-W 115Vac	115V~ 2,5VA	DPCO	yes	yes	C
TCV-W 24Vac	24V~ 2,5VA	DPCO	yes	yes	C
TCV-W 24Vdc	24V= 2W	DPCO	no	yes	C

* The measurement input is galvanically isolated from the power supply

